CITY OF SUFFOLK – DEPARTMENT OF PLANNING & COMMUNITY DEVELOPMENT
DIVISION OF PLANNING

STREET LIGHT REQUEST SUMMARY **SEE PRINTS FOR DETAILS** **Date:** _____

CITY PROJECT # / LOCATION **REF:** _____ **Phone #:** _____

_____

_____

Install Quantity	Type of Pole	Mounting Height	Type of Fixture	Size of Light	Bracket Length

If Applicable:

Remove Quantity	Size of Lights (specify MV or SV)

COMMENTS: _____

_____

_____

_____

PLEASE NOTE: Flat lenses shall be utilized (as opposed to drop lenses) for the enclosed (cobra) and ultra fixture types.

POLE TYPES:	VALID MOUNTING HEIGHTS	STANDARD BRACKETS
WOOD	25’, 30’, 35’, 40’	30”, 6’, 8’, 10’, 12’, 14’, 16’, 18’, 20’
ALUMINUM	30’, 35’, 40’	6’, 8’, 10’, 12’
ALUM. FOR BRIDGE	30’	6’, 8’
CONCRETE	10’, 14’ ** 25’, 30’, 35’, 40’	30”, 6’, 8’, 10’, 12’
FIBERGLASS	10’, 14’ ** 25’, 30’, 35’, 40’	30”, 6’, 8’, 10’, 12’
SIGNAL POLE	--specify pole height--	--specify bracket length and #--

* Please, note bracket lengths 12’ and greater may require guying.
** Mounting heights less than 20’ use pole-top fixtures only (no brackets).

FIXTURE TYPES	AVAILABLE LIGHT SIZES
OPEN VERTICAL	70 / 100 / 150 watts HPSV
ENCLOSED (COBRA)	70 / 100 / 150 / 250 / 400 watts HPSV
**COLONIAL	70 / 100 / 150 watts HPSV
**CONTEMPORARY	70 / 100 / 150 watts HPSV
**ACORN	70 / 100 / 150 watts HPSV
**TRADITIONAL	70 / 100 / 150 watts HPSV
**DECORATIVE	70 / 100 / 150 watts HPSV
ULTRA	70 / 100 / 150 / 250 / 400 watts HPSV
DIRECTIONAL	400 watts HPSV