

CITY OF SUFFOLK

DEPARTMENT OF PLANNING AND COMMUNITY DEVELOPMENT 442 W. WASHINGTON ST., SUITE 1084A, SUFFOLK, VIRGINIA 23434 PHONE (757) 514-4150 FAX (757) 514-4199

DEMOLITION/MOVING UTILITY SIGN-OFF FORM

Prior to the issuance of this permit, all utilities <u>MUST</u> be disconnected from the structure. This form <u>MUST</u> be signed by the utilities representative and returned to this office. APPLICANT/OWNER: _____ CONTACT # _____ MAILING ADDRESS OF APPLICANT/OWNER: ADDRESS OF STRUCTURE TO BE DEMOLISHED OR MOVED: PARCEL # TAX MAP # PLEASE CHECK THE APPROPRIATE SELECTION OF THE TYPES OF STRUCTURES THAT WILL BE DEMOLISHED: ☐ All structures on the above referenced property. ☐ Part/portion of the structures on the above referenced property. If you selected this option please provide a detailed description of the structures that are to be demolished: *Does the home contain lead paint? **YES** or **NO** If yes, please proceed: *Is the scope of work EPA compliant? YES or NO RRP Certification # Expiration Date: *Is the contractor RRP certified? **YES** or **NO** NOTICE TO ALL UTILITY COMPANIES: The above applicant is applying for a demolition or moving permit, all utilities MUST be removed from the structure prior to the permit being issued, this, it is requested that you sign this application **AFTER** your appropriate utilities have been removed. GAS COMPANY REPRESENTATIVE: Printed Name Signature Contact # **ELECTRIC COMPANY REPRESENTATIVE:** Printed Name Signature Contact # TELEPHONE COMPANY REPRESENTATIVE: Printed Name Signature Contact # CITY OF SUFFOLK, PUBLIC UTILITIES: Printed Name Signature Contact # **CABLE TELEVISION REPRESENTATIVE:** Printed Name Signature Contact # 112.1.4 - Asbestos inspection prior to permit issuance; certification for re-occupancy. The building official shall not issue a building permit allowing a building for which an initial building permit was issued before January 1, 1985, to be renovated or demolished until the building official receives certification from the owner or his agent that the affected portions of the building have been inspected for the presence of asbestos by an individual licensed to perform such inspections pursuant to 54.1-503 of the Code of Virginia and that no asbestos-containing materials were found or that appropriate response actions will be undertaken in accordance with the requirements of the Clean Air Act National Emission Standard for the Hazardous Air Pollutant (NESHAPS; 40 CFR Part 61, Subpart M), and the asbestos worker protection requirements established by the U.S. Occupational Safety and Health Administration for construction workers (29 CFR1926.1101). Local educational agencies that are subject to the requirements established by the Environmental Protection Agency under the Asbestos Hazard Emergency Response Act (AHERA) shall also certify compliance with 40 CFR Part 763 and subsequent amendments thereto. To meet the inspection requirements above, except with respect to schools, asbestos inspection of renovation projects consisting only of repair or replacement of roofing, floorcovering, or siding materials may be satisfied by a statement that the materials to the repaired or replaced are assumed to contain friable asbestos and that asbestos installation, removal, or encapsulation will be accomplished by a licensed asbestos contractor. The provisions of this section shall not apply to single family dwellings or residential housing with four or fewer units, unless the renovation or demolition of such buildings is for commercial or public development purposes. The provisions of this section shall not apply if the combined amount of regulated asbestos-containing material involved in the renovation or demolition is less than 260 linear feet on pipes or less than 160 square feet on other facility components or less than 35 cubic feet off facility components where the length or area could not be measured previously. An abatement area shall not be reoccupied until the building official receives certification from the owner that the response actions will be completed and final clearances will be measured. The final clearance levels for reoccupancy of the abatement area shall be 0.01 or fewer asbestos fibers per cubic centimeter if determined by Phase Contrast Microscopy analysis (PCM) or 70 or fewer structures per square millimeter if determined by Transmission Electron Microscopy analysis (TEM).

SIGNED	PRII	NT NAME	
DATE	Check Appropriate Box:	□ Owner □ Contractor □ Agent	rev. 1/12/2017